

KM 290-HRS-V2

Kiosk Module

Specifications

KM290-HRS-V2

Printing method	Thermal dot-line printing
Number of dots	432
Resolution (dots/mm)	8
Paper width (mm)	60 or 66 ± 0.5
Printing width (mm)	54
Paper loading	Automatic
Max. paper weight (g/m ²)	100
Printing speed (mm/s)	80
Paper roll diam. max. (mm)	140
Recommended Paper	JUJO AF50KS-E3, Koehler KT100P, Kanzan KPW460 or equivalent
Printing life	100 km/100M pulses
Cutter life	Min 500K cuts
Dimensions (WxHxD mm)	116x175x111 (with default paper holder ass.bly position)
Weight (g)	800
Operating temperature (°C)	-10 to +60 °C
Character set	3 resident + downloadable
Character size	8x16 / 7x16 / 12x20
Interfaces	RS232; USB (2.0)
Voltage Range	12 to 27 V programmable
Current Consumption (A)	From 1 to 8
Graphics	3 modes
Barcodes	UPC A-E, EAN 13-8, Code 39, ITF 2/5, Codabar, Code 128 A-B-C
Sensor	Near End Of Paper / End Of Paper / Head Up / Paper exit detection
Drivers	Windows, Linux
Label/Black mark detection	Y
Functional keyboard	Y



60 mm
66 mm

Features

- 2 inch paper width
- Compact and light
- Print text, graphics and 11 barcodes
- Vertical and horizontal printing
- Multi position (3) Paper Roll support
- Integrated switches and LED (on-off line status, paper feed)
- 2 Communication ports
- Programmable energy consumption
- Three resident fonts
- Downloadable character set
- Powerful Graphic Modes
- Hole/Mark Detection/Correct Paper Path Exit / NEOP Detection sensor
- Guillotine cutter (full & partial cuts)

Applications

- ATM machines
- Data terminals
- Gaming and lottery
- Gas pumps
- ID automation
- Kiosks
- Parking
- Vending Machines
- Ticketing

Options

- Windows Drivers
- Linux Drivers
- Label / black mark detection sensor